

Thickness Gauges according to International Standards

	D-1000	D-2000	D-2005	D-2006	D-2010	D-2020
Display	LCD	LCD	LCD	TFT	TFT	TFT
Motorized feeler movement			x	x	x	x
Display illumination				x	x	x
Unit mm/inch switchable	x	x	x	x	x	x
Auto. zero adjustment				x	x	x
Single measurement	x	x	x	x	x	x
Measuring cycles (series of measurements)					x	x
Preselection of hoist level				x	x	x
Adjustable residence time				x	x	x
Adjustable MIN/MAX values					x	x
Statistical evaluation (numeric)				x	x	x
Statistical evaluation (graph)					x	x
Automatic material feed						x
Connection for foot pedal			x	x	x	x
Digital interface	x	x	x	x	x	x
Software	SW-50 optional	SW-50 optional	SW-50 optional	SW-52 optional	SW-52 inclusive	SW-52 inclusive
Resolution standard Resolution option	0.01 mm 0.001 mm	0.01 mm 0.001 mm	0.01 mm 0.001 mm	0.01 mm 0.001 mm	0.001 mm	0.001 mm
Measuring range standard Measuring range option	0-10 mm 0-25 and 25-50 mm	0-10 mm 0-25 or 0-50 mm				0-10 mm 0-25 mm
Dimensions in mm (measuring range 25 mm)	250x180x400	300x240x300	300x210x300	300x200x300	300x200x300	300x300x320
Weight in kg (measuring range 25 mm)	approx. 12 kg	approx. 23 kg				approx. 31.5 kg